

C4050 UHF

Mobile Computer

Chainway's C4050UHF mobile computer provides high performance UHF RFID reading/writing capability. It is designed to support EPC C1 GEN2 / ISO18000-6C protocol, and equipped with class leading R2000 UHF module or costeffective UHF module that covers frequency ranges for most areas. This versatile device can also be configured with class leading high performance 1D/2D barcode scanning and a variety of wireless connections such as Bluetooth, 3G, and WiFi. With its highly customizable ability, enterprises can deploy this single device in many areas, including asset management, retail, warehouse management, fleet management and etc.











Most Powerful Application Performance

The C4050UHF is based on Android 4.4.2 system, features the fast and powerful quad core 1.3GHz processor, together with 1GB of RAM, 4GB build-in flash storage, plus a SD card slot that can add up to 32GB of memory.



Extensive Data Capture Functions

The C4050UHF can also be integrated with best-inclass Motorola 1D/2D barcode scanning engine, sensitive fingerprint snap-on and GPS. It allows users to choose data collection options as per industry need.



Powerful Battery

With the embedded 3200mAh main battery and the 5200mAh pistol battery, the C4050UHF enables non-stop operation over the full working day.



Superior UHF RFID Reading Capability

The C4050UHF provides new levels of UHF RFID reading performance. It can be configured with class-leading R2000 UHF module or cost-effctive UHF module, together with two kinds of high performance antenna options.



Fast Wireless Connectivity

Whether indoors or outdoors, the C4050UHF provides fast and stable network connectivity with a variety of wireless connections including WCDMA, WiFi, Bluetooth and GPRS.



Highly Customizable

From a single function device to a fully featured enterprise mobile computer, this device delivers the best possible flexibility and diversity to satisfy a whole variety of application needs.

About Chainway

CHAINWAY®



1D Barcode



2D Barcode



RFID





3G







GPS

WiFi

Bluetooth

$\Delta \subset$	00	22	ries



AC Adapter



Snap-on



USB cable



Cradle



Pistol



Fingerprint Snap-on (Optional)

Physical Char	Physical Characteristics	
Dimensions	213mm x 87mm x 151mm/ 8.39 x 3.43 x 5.94in	
Weight	456g/16.08oz	
Display	4'' WVGA (480*800), 16.7M colors	
Touch Panel	Rugged capacitive touch panel	
Power	Main battery: Li-ion, 3200mAh	
1 OWCI	Pistol battery: Li-ion, 5200mAh	
Expansion Slot	1 PSAM, 1 SIM, 1 MicroSD(TF) slot	
Interfaces	USB Micro-B	
Audio	0.5W speaker, build-in microphone	
Keypad	Numeric / Qwerty	
Sensors	Light Sensor, Proximity Sensor	
Performance		
CPU	Cortex-A7 1.3GHz quad-core	
RAM	1GB	
ROM	4GB	
Expansion	Supports up to 32GB Micro SD card	

Developing E	Developing Environment	
Operating System	Android 4.4.2	
SDK	Chainway Software Development Kit	
Language	Java	
Tool	Eclipse / Android Studio	
User Environm	nent	
Operatina Temp.	14°Fto 122°F / -10°C to 50°C	

Operating Temp.	14°Fto 122°F / -10°C to 50°C
Storage Temp.	-40°F to 158°F / -40°C to 70°C
Humidity	5%RH - 95%RH non condensing
D C	Multiple 1.2m drops to concrete across the
Drop Specification	operating temperature range
Tumble Specification	1000 x 0.5m/1.64ft falls at room temperature
Sealing	IP64
Camana mia mitan	

Communicat	ion
WLAN	IEEE802.11 b/g/n
	GSM/GPRS/EDGE Quad Band
WWAN	(850/900/1800/1900MHz)
	WCDMA (850/1900/2100MHz)
Bluetooth	Bluetooth 4.0
GPS	GPS, AGPS

Barcode Scar	nning (Optional)
1D Linear Scanner	
1D Laser / CCD	Symbol SE965/EM-1350
	UPC/EAN, Code128, Code39, Code93, Code11,
Symbologies	Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of
	5, Codabar, MSI, RSS, etc.
2D Imager Scanner	
2D CMOS Laser Scanner	Symbol SE4750
	PDF417, MicroPDF417, Composite, RSS, TLC-39,
	Datamatrix, QR code, Micro QR code, Aztec,
Symbologies	MaxiCode; Postal Codes: US PostNet, US Planet,
	UK Postal, Australian Postal, Japan Postal, Dutch
	Postal (KIX), etc.
RFID	
UHF	
Frequency	865MHz-868MHz / 920-925MHz / 902-928MHz
Protocol	EPC C1 GEN2 / ISO18000-6C

0111		
Frequency	865MHz-868MHz / 920-925MHz / 902-928MHz	
Protocol	EPC C1 GEN2 / ISO18000-6C	
Antenna	Linear polarization (1.8dBi)	
	Circular polarization (2.5dBi)	
Power	1W (+10dBm to +30dBm)	
	Option1 (R2000), up to 4.5m	
R/W ranges	Option2, up to 2m	
	(Ranges depend on tags and environment)	
Biometric (Or	otional)	

Biometric (Or	metric (Optional)		
Functions	Enrollment, compare, deletion etc.		
Sensor	TCS2SS		
Sensor Type	Capacitive Sensor		
Resolution	508DPI		
Memory	1,000 PCS fingerprints		
PSAM (Optional)			

PSAM (Optional)		
Slots	1 PSAM slot	
Protocol	ISO7816	

Notice:Product specifications are subject to change without notice. / Version:C4050UHF V2.0.2 / Update Date:2016-08-22

CHAINWAY®

Shenzhen Chainway Information Technology Co., Ltd
Address:9F,Building2,Phase 2,Gaoxinqi Industrial Park, Liuxian 1st Rd.,Bao'an District,Shenzhen, Guangdong 518102, China Tel:0086-755-23223316 Fax:0086-755-23223310
Email:business@chainway.cn Web:http://www.chainway.net

